

Supreme[®]
People who know plastics best



Supreme Always Value Efficient

DURAfloorprotector

High strength product for floor protection

DURAFloorprotector

High strength product for floor protection

DURAFloorprotector

DURAFloorprotector is a high-performance composite of high-strength cross-laminated film and cushioning foam for floor protection. It is an engineered solution with a composite 3 layer structure. Layer 1 is an abrasion-resistant, high-strength film to ensure long product life. Layer 2 is of high-density polyethylene foam for cushioning purpose and layer 3 is a reinforced non-dusting and non-staining film for better grip on tiles.

Due to its enhanced properties DURAFloorprotector is offered as a better alternative product to conventional products like paper, POP, cloth etc. It provides cushioned universal floor protection for wood, ceramic and vinyl floors during construction.

Features & Benefits

- Excellent cushioning with high mechanical strength
- Good abrasion resistance on top surface
- Availability in roll form ensures very easy laying on tiles
- Very low memory retention
- Flexible - can be cut to fit in any space. Also covers all the corners as well as skirting very easily
- Environment friendly and 100% recyclable
- Anti-slip properties provide a safe work environment
- Hassle-free compared to POP, rosin paper, plastic runners or drop cloths
- Does not absorb paint, oil, grease and cleaning agents
- Does not promote growth of bacteria & fungi
- Inert - No effect of chemicals
- Lightweight and reusable - easy to installed and can be carried from site to site

Technical Specifications

Thickness	Elongation % (Min 150)	Tear strength kg/cm (Min 1.5)	Puncture resistance (Cross-laminated film side)
2 mm	366-369	6.4 -7 .3	370 gms pass
3 mm	368-369	5.2 - 6.6	520 gms pass
4 mm	366-369	4.1 - 4.7	460 gms pass
5 mm	207-370	3.0 - 3.8	580 gms pass

Applications

- Keep job site floors safe from damage and debris. DURAFloorprotector is reusable, reversible surface protection for the professional builder and craftsman
- Protects concrete, marble, granite and other counter surfaces
- Provides cushioned universal floor protection for wood, ceramic, and vinyl floors during construction
- Protects hardwood, ceramic tile, linoleum and carpet floors from damage during construction or remodeling
- Protects sinks and tubs during building or remodeling
- Protects walkways and decks during home repairs

Available in

- Thicknesses: 2 mm, 3 mm, 4 mm and 5 mm
- Width: 1400 mm
- Length: 2 mm in 120 mtrs.
3 mm in 95 mtrs.
4 mm in 75 mtrs.
5 mm in 75 mtrs.
- Variants: DURAFloorprotector-sg
DURAFloorprotector-ws

Laying procedure

Clean the floor surface of any dust particles or grease. Wet mop the floor. Then, lay DURAFloorprotector on the floor. Seal the butt joint with a 50mm BOPP tape (Double sided tape can be used if required). Terminate DURAFloorprotector over the skirting with adhesive tape.

Connect with us

Corporate Office Mumbai: Tel.: (+91-22) 40430000/ 67710000/ 30840000 Fax: (+91-22) 40430099 / 67710099 / 30840000 **Ahmedabad:** Tel.: (+91-79) 27681361 / 27680043 / 27680903 Fax: (+91-79) 27680064 **Bengaluru:** Tel.: (+91-80) 22215475 / 22104698 Fax: (+91-80) 22104697 **Chennai:** Tel.: (+91-44) 43851500 / 39811176 / 39811174 Fax: (+91-44) 43850498 **Delhi:** Tel.: (+91-11) 46590000 / 26413728 / 26217454 Fax: (+91-11) 46561393 **Hyderabad:** Tel.: (+91-40) 23221140 Fax: (+91-40) 23221120 **Kolkata:** Tel.: (+91-33) 24858837 / 24858839 / 24858833 Fax: (+91-33) 24858838 **Pune:** Tel.: (+91-20) 25890538
E-mail: dura@supreme.co.in **Website:** www.supreme.co.in

THE ABOVE MENTIONED SPECIFICATIONS ARE FOR REFERENCE PURPOSES ONLY.

Disclaimer: Recommendation for the use of this product is based upon tests believed by us to be reliable. However, since we have no control over the conditions under which the goods are transported or under which the purchaser stores, handle or uses these goods, TSIL (seller) makes no warranty of any kind, expressed or implied that the goods sold shall be of the standard quality of the seller and buyer assumes all risks and liability resulting from the use of the goods. Before using, user shall determine the suitability of the product for this intended use, and user assumes all risks and liability whatsoever in connection therewith and SIL makes no warranties or representation as to the fitness of the product for any particular use. Seller neither assumes nor authorizes any person to assume for the seller any other liability in connection with the sale or use of this product, and there are no oral agreement or warranties collateral to or affecting this product. The above values measured in our laboratory do not constitute a product specification.